## Emergency Push Pad Bolt - Gleam-863-Pb

### Product Description:

- CE Marked to EN 1125.
- Certifire approved.
- Can be used on timber fire doors (up to FD120) or metal fire doors (up to FD240) up to1200mm x 2440mm tall.
- Top and bottom bolt rods can be cut to size on sit to fit each door.
- Complete with "Push" signage.
- Automatic top trips only release bolts as the door closes into the frame, protecting the flooring and frame from harm.
- 96 hours corrosion resistance.
- Completed 200,000 cycles in durability testing.
- 10 year guarantee.




### Finishes:

- Silver
- Dark Metallic Grey
- Special finish available upon request subject to minimum order quantity.

## Outside Access Device - Gleam-855-LE

### Product Description:

- CE Marked to EN 1125.
- Certifire approved.
- Can be used on timber fire doors (up to FD120) or metal fire doors (up to FD240) up to1200mm x 2440mm tall.
- Delivered with cylinder to enable door to be immediately secured or delivered without cylinder to accommodate masterkey requirements.
- Uses a standard 45mm single cylinder.
- Standardly suitable for doors up to 60 mm thick; separately available accessories are available for thicker doors.
- Bolt through screws on the internal door face are covered by a panic or emergency device.
- 96 hours corrosion resistance.
- Completed 200,000 cycles in durability testing.
- 10 year guarantee.



### Finishes:

- Silver
- Dark Metallic Grey
- Special finish available upon request subject to minimum order quantity.